

Computer Architecture Homework 8

Spring 2022, May

Problem 1 (10 points)

Choose True / False:

1. A virtual memory system that uses paging is vulnerable to external fragmentation. _____
2. One way to solve Compulsory miss is to increase the block size. _____
3. In a bare system, addresses issued with loads/stores are real physical addresses other than virtual address. _____
4. The size of the virtual address space accessible to the program cannot be larger than the size of the physical address space. _____

Problem 2 (10 points)

This question refers to an architecture using segmentation with paging. In this architecture, the 32-bit virtual address is divided into fields as follows:

3 bit segment number	13 bit page number	16 bit offset
----------------------	--------------------	---------------

Here is the relevant table (all values in hexadecimal):

Segment Table		Page Table A		Page Table B	
0	Page Table A	0	CAEF	0	C001
1	Page Table B	1	DEAB	1	D5AA
X	(rest invalid)	2	BFFE	2	A000
		3	AF11	3	BA09
		X	(rest invalid)	X	(rest invalid)

Find the physical address corresponding to each of the following virtual addresses (answer "bad virtual address" if the virtual address is invalid):

1. 0x00000000 _____
2. 0x20032003 _____
3. 0x100205BD _____

Problem 3 (30 points)

In a 34-bit machine we subdivide the virtual address into 4 segments as follows:

8 bit	7 bit	7 bit	12 bit
-------	-------	-------	--------

We use a 3-level page table, such that the first 8-bit are for the first level and so on. Assume the size of each page table is equal to one page size. (Ignore the fragments and treat it roughly as one page)

Question 1. What is the page size in such a system?

Question 2. What is the size of a page table for a process that has 256K of memory starting at address 0?

Question 3. What is the size of a page table for a process that has a code segment of 48K starting at address 0x1000000, a data segment of 600K starting at address 0x8000000 and a stack segment of 64K starting at address 0xf000000 and growing upward ?

Problem 4 (20 points)

A processor has 16-bit addresses, 256 byte pages, and an 8-entry fully associative TLB with LRU replacement (the LRU field is 3 bits and encodes the order in which pages were accessed, 0 being the most recent). At some time instant, the TLB for the current process is the initial state given in the table below. Assume that all current page table entries are in the initial TLB. Assume also that all pages can be read from and written to. Fill in the final state of the TLB according to the access pattern below. Free physical pages: 0x17, 0x18, 0x19.

1	write 0x776e
2	read 0x9796
3	write 0x9a0f
4	read 0x5a82
5	write 0x035b
6	read 0x0365

VPN	PPN	Valid	Dirty	LRU
0x6f	0x48	1	0	0
0x03	0x97	1	1	5
0x77	0x56	1	0	6
0x1f	0x2d	1	1	1
0x9a	0x9a	1	0	3
0x00	0x00	0	0	7
0xea	0x6d	1	1	2
0xc8	0x21	1	0	4

VPN	PPN	Valid	Dirty	LRU

Problem 5 (30 points)

Assume a computer has 32-bit addresses, 4KB pages, and the physical memory space is 4GB. The computer uses two-level paging, each page table entry consists of a next-level address index and seven additional control bits.

Question 1. What is the minimum number of bits per secondary page table entry? And justify your ans..

Question 2. What is the minimum number of bits per level 1 page table entry? And justify your ans..

Question 3. Assuming that each page table entry is 8 bytes in size (In addition to the next level address index and seven additional control bits, we have added some new things to expand its size to 8 bytes) and each page table is exactly 1 page in size, how many bits of virtual address does the program actually use? (Hint: It means that not all 32 bits are valid virtual addresses, and some bits may be useless.)

Question 4. According to question 3, how many bytes is the virtual address space of an application?