

Computer Architecture Homework 8

Spring 2019, May

1 Virtual memory

1. What are three specific benefits of using virtual memory?

2. What should happen to the TLB when a new value is loaded into the page table address register?

3. A processor has 16-bit addresses, 256 byte pages, and an 8-entry fully associative TLB with LRU replacement (the LRU field is 3 bits and encodes the order in which pages were accessed, 0 being the most recent). At some time instant, the TLB for the current process is the initial state given in the table below. Assume that all current page table entries are in the initial TLB. Assume also that all pages can be read from and written to. Fill in the final state of the TLB according to the access pattern below

Free physical pages: 0x17, 0x18, 0x19

Access pattern:

Read	0x11f0
Write	0x1301
Write	0x20ae
Write	0x2332
Read	0x20ff
Write	0x3415

Initial TLB:

VPN	PPN	Valid	Dirty	LRU
0x01	0x11	1	1	0
0x00	0x00	0	0	7
0x10	0x13	1	1	1
0x20	0x12	1	0	5
0x00	0x00	0	0	7
0x11	0x14	1	0	4
0xac	0x15	1	1	2
0xff	0x16	1	0	3

Final TLB:

VPN	PPN	Valid	Dirty	LRU

2 Hamming ECC

Recall the basic structure of a Hamming code. Given bits $1, \dots, m$ the bit at position 2^n is parity for all the bits with a 1 in position n . For example, the first bit is chosen such that the sum of all odd-numbered bits is even.

Bit	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Data	<u>P1</u>	<u>P2</u>	D1	<u>P4</u>	D2	D3	D4	<u>P8</u>	D5	D6	D7	D8	D9	D10	D11
P1	X		X		X		X		X		X		X		X
P2		X	X			X	X			X	X			X	X
P4				X	X	X	X					X	X	X	X
P8								X	X	X	X	X	X	X	X

1. How many bits do we need to add to 0011_2 to allow single error correction?
2. Which locations in 0011_2 would parity bits be included? (Use P for parity bits)
3. Which bits does each parity bit cover in 0011_2 ?
4. Write the completed coded representation for 0011_2 to enable single error correction.
5. How can we enable an additional double error detection on top of this?

6. Find the original bits given the following Single-Error Correction(SEC) Hamming Code: 0110111_2

7. Find the original bits given the following SEC Hamming Code: 1001000_2

8. Find the original bits given the following SEC Hamming Code: 010011010000110_2

3 Availability

1. In this example, a Warehouse-Scale Computers (WSC) has 55,000 servers, and each server has four disks whose annual failure rate is 4%. How many disks will fail per hour?

2. What is the availability of the system if it does not tolerate the failure? Assume that the time to repair a disk is 30 minutes.

3. Which of the following will decrease availability? **Circle** them.

A. decrease MTTF

B. increase MTTF

C. decrease MTBF

D. increase MTBF

E. decrease MTTR

F. increase MTTR

4 Memory Mapped I/O

Certain memory addresses correspond to registers in I/O devices and not normal memory

0xFFFF0000 – Receiver Control:

LSB is the ready bit, there may be other bits set that we don't need right now

0xFFFF0004 – Receiver Data:

Received data stored at lowest byte.

0xFFFF0008 – Transmitter Control:

LSB is the ready bit, there may be other bit set that we don't need right now.

0xFFFF000C – Transmitter Data:

Transmitted data stored at lowest byte

Finish the RISC-V code to read a byte from the receiver and immediately send it to the transmitter.

```
1
2 -----
3 receive_wait:
4 lw t1 0(t0)
5
6 ----- # poll on ready of receiver
7
8 -----
9 lb t2 4(t0) # load data
10 transmit_wait:
11 lw t1 8(t0)
12
13 ----- # poll on ready of transmitter
14
15 -----
16
17 ----- # write to transmitter
```